

skeye.pad

THE SMART COMPANION

The successful skeye.pad range provides impressive high performance functionality and supports an exceedingly wide range of applications in the field service and logistics sector.





TAILOR-MADE SOFTWARE TOOLS KEEP OPERATING AND DEVELOPMENT COSTS LOW

APPLICATIONS OVERVIEW

- Order management
- Data capture
- Warehouse logistics

FIELDS OF APPLICATIONS

- Field service
- Logistics
- Hospitality

Its Marvell PXA255 CPU with 400 MHz and 128 MB RAM as well as 128 MB flash memory (opt. 1 GB) means that the **skeye.pad** also supports complex applications. Thanks to the operating system Windows CE 5.0 the versatile terminal can be easily integrated into existing IT infrastructures. The **skeye.pad** has a PCMCIA, CF and SD card slot, making it extremely flexible and additional periphery devices can be connected via USB- and RS 232-ports. A broad range of tailor-made Skeye software tools simplify the creation of applications as well as the maintenance and care of the system and thus keeps the operating and development costs low.

Simply efficient

The **skeye.dart** is the ideal companion in many applications. The especially large 8.4" display is ideally suited for providing an above-average depiction of complex data and graphics, and makes the 900 g terminal an indispensable working tool boasting a particularly wide range of applications.

Flexible

The **skeye.pad** automotive is fitted permanently in the vehicle and optimally supports all modern applications in the logistics field. In addition, **skeye.pad** automotive allows the user to connect a reversing camera, thus providing even greater safety in use.





Product variants


Accessories

 <p>skeye.pad XSL</p>	 <p>Charging station</p>
 <p>skeye.pad XSL with swivel head for fixed mounting in the vehicle</p>	 <p>Desktop cradle</p>
 <p>skeye.pad automotive</p>	 <p>Car cradle</p>  <p>Pouch with belt clip</p>



TECHNICAL DATA

System	<ul style="list-style-type: none"> • Marvell PXA255 CPU, 400 MHz • 128 MB SD-RAM, 128 MB flash, (opt. 1 GB) • 213 mm (8,4") SVGA TFT, 800 x 600, touch screen • Windows CE .NET 4.2 or Windows CE 5.0 • Silicon Motion graphics accelerator with 8 MB memory
Communication options	<ul style="list-style-type: none"> • WLAN IEEE® 802.11b/g (not in combination with SD slot) <ul style="list-style-type: none"> – Security: WPA2, WPA – Authentication: 802.1x – Encryption: AES, TKIP, WEP – Alternative: CF slot equipped with Summit SDC-CF10AG: IEEE® 802.11a/b/g – WiFi certified, CCX v4 compatible
Interfaces	<ul style="list-style-type: none"> • USB Host, USB Device • RS232 • PCMCIA slot type II • CF slot type II • SD slot (not in combination with built-in WLAN)
Auto ID options	<ul style="list-style-type: none"> • 1D laser scanner (opt.)
Environment	<ul style="list-style-type: none"> • Operating temperature: –10 °C bis +50 °C
Weight/dimensions	<ul style="list-style-type: none"> • ≈ 900 g • 240 x 160 x 30 (L x W x H in mm)
Accessories	<ul style="list-style-type: none"> • Battery: 7,4V/3600 mAh • Desktop cradle incl. USB cable (Device) • Replacement battery • Battery charger (holds 1 battery) • Car cradle: <ul style="list-style-type: none"> – Access for GPS mouse – 1 x RS 232, 1 x USB Host – Cigarette lighter connector with 5 A fuse • Navigation software <ul style="list-style-type: none"> – Map & Guide Truck Navigator – skeye.guide • Various cases

 **Skeye** (Headquarters)
 Rotenburger Str. 20
 30659 Hannover
 +49 511 6102-0
 +49 511 6102-411 Fax
 info@skeye.com
 www.skeye.com

 **Skeye** Italy
 Via Cavriana, 3
 20134 Milan
 +39 02 7391-218
 +39 02 7391-256 Fax
 info@skeye.com
 www.skeye.com

 **Skeye** UK
 Westmead Industrial Estate
 Westlea, Swindon, SN5 7AD
 +44 1793 647-800
 +44 1793 647-802 Fax
 info@skeye.com
 www.skeye.com

 **Skeye** USA
 12905 S.W. 129th Avenue
 Miami, FL 33186
 +1 305 909-0173
 +1 305 596-7222 Fax
 info@skeye-usa.com
 www.skeye-usa.com